



IMPORTANT: SEE DRAWING D-600-0059 FOR FRAMING REQUIREMENTS

**TNR INDUSTRIAL DOORS INC.**

**SHOP DRAWING, MODEL HDXL 9, LEFT HAND**

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES	EXT. DETAIL: DOOR MT. OPERATOR & C/BAL SPRINGS	
<input type="checkbox"/> - *** GALV. DOOR HOODS	<input type="checkbox"/> - RELAY LOGIC CONTROLS	- SPEED AS SHOWN	LIMITATIONS: (OW <= 20' 0") & (30' 0" < OH <= 45' 0")	
<input type="checkbox"/> - 16" x 16" WINDOWS, QTY. _____	<input type="checkbox"/> - FUSED DISCONNECT	- NEMA 4, WALL MOUNTED CONTROL PANEL	DATE DR'N: FEB. 05, 2010	REVISION: RELEASE
<input type="checkbox"/> - BLUE EPDM CURTAIN	<input type="checkbox"/> - LOOP DETECTOR	- NEMA 4 LIMIT BOX ON OPERATOR	DRAWN BY: R.B.	DRAWING No.: D-600-0057
<input type="checkbox"/> - GRAY EPDM CURTAIN	<input type="checkbox"/> - WIRELESS RECEIVER (OCS)	- 50,000 CYCLE COUNTERBALANCE SPRINGS	ELECTRICAL CRITERIA:	
<input type="checkbox"/> -	<input type="checkbox"/> - WIRELESS TRANSMITTER (OCS), QTY. _____	- REVERSING EDGE	CONTROL PANEL NEMA/EEMAC 4 STD. OR _____	
<input type="checkbox"/> -	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- THRU-BEAM PHOTOEYE	PRIMARY POWER SUPPLY: _____ Volts, 3 Phase, 60 Hertz	
<input type="checkbox"/> -	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- 5" HIGH, BLACK EPDM RUBBER LOOP	OPERATOR CRITERIA: HG, HIGH EFFICIENCY HELICAL GEAR	
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- NEWGEN II GUIDE AND CURTAIN LOK SYSTEM	LIMIT BOX NEMA/EEMAC 4 STD. OR _____	
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- PROGRAMMABLE CONTROLLER	_____ HP, DOOR SPEED: OPEN & CLOSE @ _____ ips	
<input type="checkbox"/> -	<input type="checkbox"/> - CONSTANT PRESSURE CLOSE	- GUIDE GUARDS - 8 FT HIGH	END USER:	
<input type="checkbox"/> -	<input type="checkbox"/> -	- STATIONARY WINDBAR	DEALER:	
<input type="checkbox"/> -	<input type="checkbox"/> -	-	DOOR SIZE:	SERIAL No.: